



C-835030S

DISC DIAMETER	254.0 [10.00]	304.8 [12.00]	355.6 [14.00]	406.4 [16.00]
TORQUE (STATIC)	79 N-M [700 IN-LBS]	98 N-M [866 IN-LBS]	166 N-M [1,032 IN-LBS]	135 N-M [1,198 IN-LBS]
RELEASE PRESSURE	2.8 BAR [40 PSI]	2.8 BAR [40 PSI]	2.8 BAR [40 PSI]	2.8 BAR [40 PSI]

GEOMETRIC TOLERANCE VALUES		THIRD ANGLE PROJECTION	
MM	INCH		
.013	.0005		
.03	.001		
.05	.002	SURFACE ROUGHNESS VALUES	
.08	.003	μm	μin
.13	.005	6.3	250
.20	.008	3.2	125
.25	.010	1.6	63
.38	.015	0.8	32
		0.4	16
		0.2	8

- UNLESS OTHERWISE SPECIFIED**
- METRIC TOLERANCES: X ±0.8; .X ±0.5; .XX ±0.13
INCH TOLERANCES: .XX ±.02; .XXX ±.005
 - ANGLES ±5°
 - PRIMARY DIMENSIONS ARE IN MM
SECONDARY DIMENSIONS ARE IN INCHES
 - DO NOT SCALE DWG - WORK TO DIMS
 - PRODUCT MUST CONFORM TO ENGINEERING STANDARD WORK INSTRUCTIONS

nexen Nexen Group, Inc.

TITLE GENERAL DIMENSIONS

MODEL DBSE*3 SPRING,HCO.,250 DISC,WITH BRACKET

43889	19646	7/13/2011
ERO	ECO	DATE

DWN TRW DATE 7/11/2011 SCALE: 1:1 SHEET 1 OF 1

CHKD TGH DATE 7/12/2011

APVD CDV DATE 7/13/2011

C-835030S REV H