



The Right Connection®

Data Sheet

Garden Hose Fittings



Garden Hose Fittings

500	Garden Hose Accessory Products
501	Female Hose x Female Pipe - non swivel
501-SS	Female Hose x Female Pipe - non swivel, 303 SS
502	Female Hose x Female Pipe - swivel
502-SS	Female Hose x Female Pipe - swivel, 303 SS
503	Female Hose x Male Pipe - non swivel
503-SS	Female Hose x Male Pipe - non swivel, 303 SS
504	Female Hose x Male Pipe - swivel
504-SS	Female Hose x Male Pipe - swivel, 303 SS
506	Female Hose x Female Hose - swivel
507	Male Hose x Female Pipe
507-SS	Male Hose x Female Pipe - 303 SS
508	Male Hose x Male Pipe
508-SS	Male Hose x Male Pipe - 303 SS
509	Male Hose x Male Hose
509-SS	Male Hose x Male Hose - 303 SS
513	Hose Cap
514	Male Hose x Male Pipe x Female Pipe
514-SS	Male Hose x Male Pipe x Female Pipe - 303 SS
572	Lok-On Male
574	Lok-On Female
575	Lok-On Set
578	Garden Hose Mender
585	Short Shank Male
586	Short Shank Female Swivel - round nut
587	Short Shank Set (male and female swivel) - round nut
588	Short Shank Female Swivel - hex nut
589	Short Shank Set (male and female swivel) - hex nut
590	Garden Hose Male
590-SS	Garden Hose Male - 303 SS
591	Garden Hose Female Swivel
591-SS	Garden Hose Female Swivel - 303 SS
592	Garden Hose Set (male and female swivel)
592-SS	Garden Hose Set (male and female swivel) - 303 SS
593	Long Shank Male
594	Long Shank Female Swivel
595	Long Shank Set (male and female swivel)

Compliances:

- FED-STD-H28/10 NH, NPSH
- SAE J530, NPT, NPTF

Compatible Hoses:

- All Swan, Colorite, Flexon, Ames, Teknor Apex and other designated water and garden hoses

Materials:

- Brass Fittings: Alloy 360
- Brass Forged Accessories: Alloy 370
- Brass Cast Accessories: Alloy 3604
- Brass: Alloy CA2745 or C46400 for Lead Free Brass (parts ending in LF)
- Stainless Steel : 303 SS
- Plating: optional electroless nickel
- Washers - NBR, SBR and FDA Black PVC Duro

Performance:

- Temperature rating: +34°F to +195°F
- Pressure rating: 150 PSI maximum
- Exceptions:

500QCF: 140°F	500BFP: 140°F – 100 PSI
500QCFV: 140°F	500GHV: 140°F – 100 PSI
500QCSG: 140°F	500GHY: 140°F – 100 PSI
500QCK: 140°F	500GH4VBK: 120°F – 100 PSI
500QCKV: 140°F	500YC: 140°F - 100 PSI

- * Vacuum – not rated

Applications / Markets:

- Industrial, irrigation, landscape, marine, car wash, contractor, farm and ranch, parks, nurseries, golf course, dairy, restaurant and brewery washdown.

Strengths / Features:

- Hex and round nut products
- Solid and swivel adapters
- Size range from 3/8" to 1" for most products
- 85 available products
- Special sizes, configurations and thread specifications available on request

Price Advantage:

- Available Volume Discount Program

Note:

- Not intended for use in potable water systems unless using Lead Free products (parts ending in LF)

Dixon Brass

ph 800.323.4440

fx 800.628.7259

customer.service@dixonbrass.com

dixonvalve.com